

LOCAL EXTRACTOR



White design



**Stainless steel
suction nozzle**

R
2000, 3000,
4000
with gas spring

Local extractor for all kinds of worksites where flexible design and efficient extraction are important

The FUMEX local extractor R, with lengths 2, 3 and 4 m, has a stable construction and is equipped with a gas spring that balances the dead weight of the arm. For this reason the R is extremely easy to handle at the same time as it stays without rebounding when positioned, even in the outer positions.

The FUMEX R may easily be adapted to different uses with e.g. five different hose diameters as standard. Different hose qualities may also be chosen for most kinds of aggressive chemicals, as well as stainless steel suction nozzle and hood.

FUMEX always designs its local extractors with supporting arms on the outside, which ensures a natural and undisturbed air flow. In addition, the pressure drop will be low and there is hardly any risk of ducts being blocked. The R may also be equipped with a flat screen hood for even greater efficiency. A conical hood, with or without halogen light, is also available.

Adjustments of joints as well as maintenance can easily be taken care of with hand tools from the outside.


The FUMEX R is easy to install and delivered with brackets for ceiling or floor mounting.

Fumex also offers a range of fans, accessories, automatic control devices and filters for our local extractors.

FUMEX®

LOCAL EXTRACTOR


Pure advantage



	A (mm)	B (mm)	C (mm)	Working radius* (mm)	Maximum radius (mm)
R-2000	120	740	990	1600	2150
R-3000	120	1140	1390	2600	2950
R-4000	1100	1140	1390	3600	3930

Ø D (mm)
75
100
125
160
200

* At a mounting height of 2.0 m and a working height of 750 mm



Hose

Made of spring steel coil completely embedded in PVC-coated polyamide fabric.
For other hose qualities, contact FUMEX.

Delivery

For easy installation, the arm is delivered fully assembled including bracket for wall mounting. Other hose qualities that can withstand aggressive chemicals or other special requirements are available on request. Accessories include stainless steel suction nozzles. Brackets for ceiling and floor mounting as well as flat screen hood or conical hood, with or without halogen light, are also available.

Hose

Qualities Non-inflammable, suitable for welding fumes and flue gas.
Temperature range -10°C to +90° C

Other information

Surface treatment of metal components Powder coating
Weight 11, 13 and 23 kg

