

Hood Positioning Device (HPD): Telescopic Extraction Arm







Hood Positioning Device (HPD): Telescopic Extraction Arm

A flexible, self supporting extraction arm, engineered to carry a range of hood and hose combinations.


- Twin supports allow simple fixing of flexible hose in various diameters
- Support clips allow the hose to be easily removed for cleaning & reinstallation
- Increased surface area of all joints gives a lighter feel to the HPD, enabling easier positioning with the HPD self supporting in its required placement
- Rear mechanism is cased for improved safety and hygiene
- Boom at the rear provides the HPD with a 270 degree pivot, improving the working radius
- Integrated damper allows greater control of the airflow in the extraction system
- ATEX compliant and Stainless Steel versions are available


Mounting Brackets:

- Standard Wall bracket
- Floor Stanchion
- Ceiling Bracket
- Finish:
- Polyester Coated Black
- Texture Conductive Black (ATEX)
- Stainless Steel

All Telescopic HPDs are offered with a unique free 5 Year Warranty. (Return to Base)

HPD Dimensions										
	HPD	Length (mm)	А	В	С	D	Max Reach	Weight (Kg)	Load Capacity	
	Retracted	1200	175	175	825	375	1550	13	3	
	Extended	1650	175	175	1225	375	1950	13	3	







www.flextraction.co.uk

Fresh Air By Design

Telephone: 01664 - 410 641